

DESTROYER

The DESTROYER is a formidable machine designed to cope with the thickest scrub and forestry re-growth. The heavy duty DESTROYER features an 8mm deck and a 70mm gearbox mounting point which are fully reinforced to protect against any metal fatigue. Beneath the deck are three huge free swinging blades, weighing 7KG each all performing like spinning axes with a tip speed of 83 metres per second.

- High Strength Steel Deck Construction
- Heavy Duty Rear Nudge Bar
- 150HP Rotor Driveline
- Front & Rear Chain Safety Curtains
- Channel Sections for Extra Reinforcement
- 7KG Blades for Axe Style Cutting
- 4 Plate Slip Clutch Protection
- Accurate Cutting Height Adjustment
- Floating Linkage
- Ideal for Reverse Drive

MODEL	DESTROYER
Cutting Width	1.90m
Overall Width	2.12m
Machine Weight	1400kg
Transport Width	2.12m
Gearbox Rating	150hp
Cutting Range	25-225mm
Number of Rotors	1
Blades	3
PTO Protection	Slip Clutch
PTO speed	1000rpm
Tractor Power Required	100hp



Spearhead
Quality - that's the point

MULTICUT 300

The no compromise mower for the most demanding of vegetation management tasks. The MULTICUT 300 is shaft driven and features the HD2 blade system for maximum lifting and cutting capacity. Specially designed under deck construction contributes to a thorough chopping of the crop and an even spread from the rear of the machine leaving a finish to be proud of.

- High Strength Steel Deck Construction
- Replaceable Full Length Skids
- 161HP Input Splitter Gearbox
- Front & Rear Chain Safety Curtains
- 8 PLY—500 x 8 Industrial Tyres
- HD2 High Lift Blade Kit
- 140MM Blade Overlap for Clean Cutting
- Input Knocking Clutch for Tractor Protection
- Shock Absorber Driveline Protection
- Rapid in Field Cutting Height Adjustment
- Floating Linkage

	MULTICUT
MODEL	300
Cutting Width	2.85m
Overall Width	3.00m
Machine Weight	1050kg
Transport Width	3.00m
Gearbox Rating	161hp & 111hp
Cutting Range	10-350mm
Number of Rotors	2
Blades	4
PTO Protection	Knocking Clutch & Rubber Shock Absorber
PTO speed	1000rpm
Tractor Power Required	50hp



Spearhead
Quality - that's the point

MULTICUT 460

Spearhead's market leading MULTICUT 460 will exceed your expectations. With three HD3 rotors each featuring the unique high lift blade design you can expect ultimate suction and a fine mulch assuring a clean cut in even the heaviest growth.

Superior strength steel decks with box section cross members provide the rugged reliability and long lasting reputation attached to this machine today.

- High Strength Steel Deck Construction
- Replaceable Full Length Skids
- 170HP Input Splitter Gearbox
- Front & Rear Chain Safety Curtains
- Puncture Resistant Industrial Tyres
- HD3 Rotors with 9 High Lift Cutting Blades
- Anti Scalp Rotor Protection Discs
- Floating Wings for Even Cutting
- Deck Protection Rings
- High Specification Slip—Clutch Protection
- Hydraulic Height Adjustment

MODEL	MULTICUT 460
Cutting Width	4.60m
Overall Width	4.80m
Machine Weight	2220kg
Transport Width	2.80m
Gearbox Rating	170hp & 111hp
Cutting Range	25-400mm
Number of Rotors	3
Blades	9 or 18
PTO Protection	Slip Clutch
PTO speed	1000rpm (540rpm Option)
Tractor Power Required	70hp



Spearhead
Quality - that's the point

QHD Range

The QHD range of flail mowers is the ultimate heavy duty grassland and vegetation maintenance tool which has proven to be a favourite for the verge mowing professional. Ideal for mounting at the front or rear of the tractor the QHD range is often used in conjunction with a Rear Mounted TWIGA to give the ultimate in verge mowing output.

Utilising a specialist C flail the quality of cut is exceptional whilst fuel consumption remains low due to the double spiral rotor arrangement.

- 2.0, 2.5 and 2.8 metre Cutting Widths
- Three Point Linkage Mounting
- Manual Adjust Front and Rear Mounting
- Manual Offset
- 110HP Bi – directional Gearbox
- 1000RPM PTO
- Adaptable for use with 540RPM PTO
- Over – run PTO Protection
- Double Skin Body
- Large Diameter Rear Roller
- Rear Roller Height Adjustment
- 0mm to 150mm Cutting Heights
- 30mm Maximum Cutting Diameter
- Hydraulic offset - option

MODEL	Q2000HD	Q2500HD	Q2800HD
Cutting Width	1.95m	2.45m	2.65m
Overall Width	2.30m	2.80m	3.00m
Transport Width	2.30m	2.80m	3.00m
Machine Weight	730kg	814kg	860kg
Cutting Range	0 - 150mm	0 - 150mm	0 - 150mm
Number of Flails	48	60	66
PTO Speed	1000rpm	1000rpm	1000rpm
Tractor Power Required	50hp	60hp	70hp

