



Technical Specification sheet

A W Blake Ltd sells a wide range of products manufactured by Redrock, from trailers to tankers. Redrock equipment is known for its heavy duty and built to last products. This sheet will provide information on a selection of products from their range. If you require further information or advice on which Redrock product is right for you, we will be happy to discuss or send information by email, post, fax or telephone.

We also have used Redrock products for sale as well as hire. Please call us for more information or email info@awblake.co.uk

BLOCKCUTTERS

- Handles grass silage, maize silage and wholecrop from the clamp.
- Models to suit all equipment, from skid steers to large telehandlers.
- Easily penetrates clamp for rapid efficient feeding.
- Extra blade on larger models to cut two small blocks, rather than one larger, unmanageable piece.

Wide ranges of bolt on industrial and tractor brackets are available. Most blockcutters can be fitted with a push off system, 'hi-lift' and rear loader masts. (Push off system is not suited for TMRs and lightweight models).



Tables of measurements for the range of block cutters models

Model- TMR Loadall	4'6"	5'2"	5'10"	6'6"
Capacity (m3)	0.95	1.10	1.25	1.35
Width (cm)	140	160	180	200
Max opening (cm)	90	90	90	90
No. of Rams	2	2	2	2
Unladen weight (kgs)	630	680	740	800

Model-Alligator	4'6"	5'2"	5'10"	7'2"
Capacity (m3)	0.95	1.10	1.25	1.50
Width (cm)	137	157	177	220
Max opening (cm)	85	85	85	85
No. of Rams	2	2	2 or 3	3
Unladen weight (kgs)	480	535	600 or 700	830

Model- Telegator	180	200	240
Capacity (m3)	1.50	1.70	2.10
Width (cm)	180	200	240
Max opening (cm)	100	100	100
No. of Rams	2	2	3
Unladen weight (kgs)	700	750	850

Model-Large Opening	140	160	180	200	300
Capacity (m3)	1.75	2.00	2.25	2.50	3.5
Width (cm)	140	160	180	200	300
Max opening (cm)	130	130	130	130	130
No. of Rams	2	2	2	2	3
Unladen weight (kgs)	900	960	1000	1060	1250

SLURRY PUMPS

Redrock slurry pumps have gained a reputation for being strong and reliable. There are three types of slurry pump on offer, each product providing the solution to your performance needs.

Standard (75hp 3000G/MIN)

- Off-set nozzle allows the slurry to be mixed in almost all directions.
- Pump can be adjusted up to 9" (300mm).
- Three point linkage 'quick attach' allows easy connection.
- No PTO disconnection required when lowering into tank.
- Suitable for tractors from 80hp.



Super Flow (100hp 3600 G/MIN)

- Mixes faster, agitates further and increases productivity, 3600 gallons/min.
- Pairing a larger ratio gearbox with a steam line pipe system, designed to reduce power loss at all stages, therefore increasing overall performance.
- No PTO disconnection required when lowering into tank.
- Suitable for tractors from 100hp.



Mega Flow (150hp 4750 G/MIN)

- Designed for the large farm and contractor.
- Halve the time taken to mix a tank, 4750 gallons/min.
- 300 degree nozzle rotation means tanks are mixed with no or minimal movement of the pump.
- Suitable for tractors from 150hp



Specifications for models

- Durable 5mm- piping for standard and super flow
- 1000 RPM PTO drive speed
- Quick release bar to ease implement attachment
- Safety grid with Height adjustment
- Galvanised as Standard
- Streamline Design
- Fits into standard safety-man holes.

Options for models

- Available in sizes: 6'6", 7', 8', 9' and 10'. (6'6" size is not available for Mega Flow)
- Top fill or mix
- Slat Lifters
- 90 degree bend c/w layflat hose
- 16' fill pipe

SLURRY TANKERS

Range of tankers are from the 1100 to 3500 tanker size (gallons).



Specifications for Tankers

- 8 & 10 stud high-speed agricultural axles
- Hydraulic brakes & handbrake
- LED Road lights
- HD rear valve
- 6mm Rolled Steel construction
- Anti- enclosure rings for durability and strength
- Quick attach suction hose
- Four fill points available
- One quick attach valve
- Hydraulic change over valve

Options

- Extra fill valves
- 20' suction hose
- 6" & 8" self-fill boom and pot system
- Sludgigator pump c/w rain gun
- Umbilical pipe fitting on sludgigator
- Over-hedge fill boom
- 8" fill valve over 6" Fill Valve
- 8" fill Valve & 8" hose over 6" Fill Valve & 6" hose
- Side spread attachment
- Wash hose (25ft & 50ft)
- Hydraulic/Air Brakes. Sprung Drawbar

AGRICULTURAL TRAILERS

Silage and Grain Trailers



Specifications

- Off centre Bogie axle
- Sprung drawbacks
- Four ram braking system
- Hard wearing hitch eye
- 65mm Bronzed bushed bogie pin with grease track
- Full road lights
- Automatic door latches
- Hose tidy
- Front ladder
- Body width tapers from 7'4" to 7'10"
- High side is the near side (LHS)
- Body length 16' to 20'
- Capacity range-10.5 tonnes to 20 tonnes.

Options

- Silage kit
- Grain chutes
- Roll over covers
- Hydraulic grain door
- Hydraulic silage door
- Air Brakes
- Dual Air/ Hydraulic Brakes
- Commercial axels
- Various wheel options

Flat Trailers



Specifications

- 8'2" Body width
- 24' to 30' Body Length
- Sprung drawbar
- 2' head board
- 4mm floor
- 4 ram Brake system
- Heavy duty tandem bogie axle
- Handbrake and Hydraulic brakes
- Strong trussed chassis

Options

- 4.5mm chequered plate floor
- Bale racks
- Extra length
- Wooden floor
- Toolbox
- ABS or load sensing

PUSH OFF BUCK RAKE

The Redrock push off buck rake is fitted with heavy duty 1400mm tines fitted in tapered sleeves for an increased service life.

- All buck rates are fitted with twin, double acting heavy-duty hydraulic cylinders
- All Pivot points are bushed and fitted with grease nipples for minimum maintenance and maximum service life.
- The hinged gate flap ensures complete discharge of the load, creating less waste, wasting less time.

Specifications

Model	Width	Push of method
12 Tine	2336mm/ 7ft 8"	Hydraulic
13 Tine	2641mm/ 8ft 6"	Hydraulic

Options

- Provision for four side tines
- 3-point linkage A-frame loader adopter
- 1500mm HT 45mm round tines.



SILAGE GRAPES

- Fitted with 1500mm 45mm round tines the grapes are designed for today's agricultural environment.
- Two sizes are available the 9ft 3" for the farmer and the hydraulic folding 12ft grape for the contractor.
- All pivot points are well bushed and are fitted with grease points to allow ease of servicing and increase working life.
- Both sizes come with side tines as standard.

Specifications

Model	No. of side tines
9ft 3"	2
12ft	4

Options

Two Sizes available

- 9ft 3" Grape for the farmer
- 12ft grape for the contractor



A.W.Blake Ltd have permission from a Redrock representative to promote Redrock products in this format.

(Due to Redrock's policy of continuous improvement Redrock reserve the right to alter the specification displayed in their brochures and website.)